



BS6500 - 2 CORE 3182Y POWER CABLE, PVC (SHEATH AND INSULATION)

Description

BS6500 - 2 CORE 3182Y POWER CABLE, PVC (SHEATH AND INSULATION)

New Surplus, Sold By Length - Per Foot

Type: 2 Core 3182Y Power Cable

A cable designed to transmit electrical power from a source to a device, often insulated for safety.

This 2-core cable is a versatile, low-voltage thin-wall multicore wiring solution designed for use in automotive, marine, and related industries. Engineered for reliability and durability, it offers exceptional resistance to challenging conditions, including exposure to petrol, diesel, oils, and diluted acids. Capable of operating at temperatures up to 105°C, this cable is ideal for demanding environments.

- **Dual-wall insulation:** Electron beam cross-linking for enhanced durability.
- **Superior resistance:** UV radiation, oils, greases, oxygen, and ozone.
- **Outstanding abrasion resistance:** Long-lasting performance.
- **Halogen-free, flame-retardant, and low-toxicity design:** Safer usage.
- **High flexibility:** Ease of stripping for convenient installation.
- **Exceptional performance:** High voltage and current carrying capacity.
- **Certified:** TUV-approved for quality and reliability.

Series: H05VV-F

Material: Pvc (Sheath And Insulation)

Details/Features: Color: Black

American Wire Gauge: 13 Awg

Cable Type: 3182Y

Conductor Material: Copper

Conductor Resistance:

7.98 ?/Km

Conductor Strand Type: Stranded

Current Rating: 25 A

Harmonised Code: H05Vv-F

Maximum Operating Temperature: 70 °C

Number Of Cores: 2

Outer Diameter: 8.86 Mm

Voltage Rating: 300 V

500 V

Product Testing: *Every product is inspected for accuracy, quality, and functionality before shipping to ensure it meets our high standards.*

Alternate Part Numbers: *With the transition from AN to MS and NAS part numbering systems, there are often multiple part numbers that meet the same specifications and performance standards. If only an alternate part number is available, we will contact you to confirm its compatibility with your application. We strongly recommend consulting the appropriate repair manuals to ensure accuracy before using an alternate part.*

Model Compatibility: *We are committed to providing accurate and up-to-date compatibility information for our parts. While the listed models reflect verified applications, this list is continually expanding. If your model isn't listed, it may still be compatible, and we encourage you to consult your repair manuals to verify the required part number before placing an order. Additionally, if you believe a model should be listed, please contact us so we can update our records accordingly.*

New Surplus: *These parts are classified as new and unused, meaning they have not been installed or placed into service. However, they come without traceability or original manufacturer certifications, which might be required for certain high-level regulatory uses. Our company provides its own Certificate of Conformance (CoC) as a statement of assurance that the parts are in good working condition and have been sourced from reliable channels. These are ideal when the focus is on cost-effectiveness without compromising on quality.*

Sold By Length - Per Foot: *This item is sold by length, Qty 1 = 1 foot, with the price listed for a single unit. Perfect for purchasing the exact quantity needed without the requirement to buy in bulk. For larger quantities, consider reviewing any available bulk pricing options.*

Date

2025/04/16

Meta Fields

Regular Price : 4.95 **Stock :** 100